

POWER SPIN-GRIT BRUSHES

These brush are used for removing soft and light scale deposits in straight, ferrous and non-ferrous internally enhanced tubes. The small diameter end of each of each brush cleans into the grooves of the tube's rifling with the ends of the brush filaments. The large diameter end of the brush cleans the lands of the tube's rifling, as well as any prime surface, with the sides of the brush filaments. Order brush to correspond to tube I.D.



Power Spin G Brush

Tube I.D.		Power Spin-Grit Brushes
INCH	MM	
1/2	12.7	BPSGB-050
5/8	15.9	BPSGB-062
3/4	19.1	BPSGB-075
1	25.4	BPSGB-100

COLOR CODED SHOOT THRU SCRUBBERS

In most cases Hard Tube Scrubbers are recommended for removing light to medium deposits in condensers order.



Tube Scrubbers by Model & Color

Tube I.D.		Scrubber O.D. (INCH)	Model	Color	Type
INCH	MM				
0.495-0.541	12.57-13.74	0.560	BTS-560-S	Yellow	Soft
0.527-0.555	13.39-14.10	0.560	BTS-560	Yellow	Hard
0.570-0.620	14.50-15.75	0.630	BTS-630-S	Brown	Soft
0.590-0.630	15.00-16.00	0.630	BTS-630	Brown	Hard
0.620-0.675	15.75-17.15	0.695	BTS-695-S	Red	Soft
0.652-0.694	16.56-17.63	0.695	BTS-695	Red	Hard
0.660-0.730	16.76-18.54	0.750	BTS-750-S	Purple	Soft
0.710-0.750	18.03-19.05	0.750	BTS-750	Purple	Hard
0.730-0.800	18.54-20.32	0.825	BTS-825-S	White	Soft
0.777-0.819	19.74-20.80	0.825	BTS-825	White	Hard
0.780-0.850	19.81-21.60	0.870	BTS-870-S	Green	Soft
0.825-0.870	20.96-22.10	0.870	BTS-870	Green	Hard
0.870-0.944	22.10-24.00	0.960	BTS-960-S	Blue	Soft
0.886-0.950	22.50-24.13	0.960	BTS-960-M	Blue	Medium
0.902-0.956	22.91-24.28	0.960	BTS-960	Blue	Hard
1.000-1.085	25.40-27.56	1.100	BTS-1100-S	Black	Soft
1.027-1.106	26.09-28.09	1.100	BTS-1100	Black	Hard

CARBIDE DRILL for Plugged Tubes/Pipes

CARBIDE DRILL are used for cleaning straight tubes plugged solidly with deposits.



Carbide Drill

Tube I.D.		Carbide Drill
INCH	MM	
1/4	6.4	BCB-025
3/8	9.5	BCB-037
7/16	11.1	BCB-043
1/2	12.7	BCB-050
9/16	14.3	BCB-056
5/8	15.9	BCB-062
11/16	17.5	BCB-068

Note : All drill run 10% oversize {e.g. CB-062 drill is .6875" (17.5mm) O.D.}

FLEX-HONE ABRASIVE TOOLS

Tube I.D.		Flex-Hone Abrasive Tools
INCH	MM	
1/4	6.4	BFHT-025
5/16	7.9	BFHT-031
3/8	9.5	BFHT-037
7/16	11.1	BFHT-043
1/2	12.7	BFHT-050
9/16	14.3	BFHT-056
5/8	15.9	BFHT-062
11/16	17.5	BFHT-068
3/4	19.1	BFHT-075
7/8	22.2	BFHT-087
1	25.4	BFHT-100

FLEX-HOSE ABRASIVE TOOLS are light pressure, soft application honing devices for straight tubes. They consist of 180 grit silicon carbide abrasive globules (stones) bonded to high density nylon filaments. They are flexible, self-compensating for wear. Their unbreakable stones are formulated to provide for a long lasting, consistent finish. Order tool to correspond to tube I.D.

Note : Flex-Hone Abrasive Tools are normally used with a water flush for maximum life.



Flex-Hose Abrasive Tools